



99101間隙式粗搪刀 - 0.03 mm/div.




尺寸範圍:
6.5mm ~ 52.5mm



0.03mm/div
可在刀具設定儀
預先調尺寸



調整範圍±0.5mm.



尺寸調整時
不用消除背隙

容易操作

- 最小刻劃0.03mm/div · 調整容易

經濟型

- 低成本可取代端銑刀或搪孔刀桿
- 更換刀片可切削各種不同材料

應用

- 容易作精搪孔前的穩定粗搪
- 精準的粗搪孔
- 可在銑床 · 切削中心機 · 特殊專用機上使用

ISO application



- * 可依加工需求訂購中心出水型頭部。
- * 可接受特殊規格訂製。

Order No.	Part No.		ØD	L1	L	刀片	螺絲 / 扳手
99101-07	SB20-0721-03		6.5 - 7.5	21	60	CC...040102	*NS-20036 0.6Nm / NK-T6
99101-08	SB20-0824-03		7.5 - 8.5	24	63		
99101-09	SB20-0927-03		8.5 - 9.5	27	65		
99101-10	SB20-1030-03		9.5 - 10.5	30	68		
99101-11	SB20-1133-03		10.5 - 11.5	33	70		
99101-12	SB20-1236-03		11.5 - 12.5	36	73	CC...060204	*NS-25045 0.9Nm / NK-T7
99101-13	SB20-1339-03		12.5 - 13.5	39	75		
99101-14	SB20-1442-03		13.5 - 14.5	42	78		
99101-15	SB20-1545-03		14.5 - 15.5	45	80		
99101-16	SB20-1648-03		15.5 - 16.5	48	83		
99101-17	SB20-1751-03		16.5 - 17.5	51	85		
99101-18	SB20-1850-03		17.5 - 18.5	50	82		
99101-19	SB20-1950-03		18.5 - 19.5	50	82		
99101-20	SB20-2050-03		19.5 - 20.5	50	82		
99101-21	SB20-2150-03		20.5 - 21.5	50	82		
99101-22	SB20-2250-03	Adjustment range:±0.5mm	21.5 - 22.5	50	82		
99101-23	SB20-2350-03		22.5 - 23.5	50	82		
99101-24	SB20-2450-03	Each Division 0.03mm	23.5 - 24.5	50	82		
99101-25	SB20-2550-03		24.5 - 25.5	50	82		
99101-26	SB20-2650-03		25.5 - 26.5	50	82		
99101-27	SB20-2750-03		26.5 - 27.5	50	82		
99101-28	SB20-2850-03		27.5 - 28.5	50	82		
99101-29	SB20-2950-03		28.5 - 29.5	50	82		
99101-30	SB20-3050-03		29.5 - 30.5	50	82		
99101-32	SB20-3250-03		31.5 - 32.5	50	82		
99101-35	SB20-3550-03		34.5 - 35.5	50	82		
99101-37	SB20-3750-03		36.5 - 37.5	50	82		
99101-40	SB20-4050-03		39.5 - 40.5	50	82		
99101-42	SB20-4250-03		41.5 - 42.5	50	82		
99101-45	SB20-4530-03		44.5 - 45.5	23	50	CC...060204	*NS-25060 0.9Nm / NK-T7
99101-47	SB20-4730-03		46.5 - 47.5	23	50		
99101-50	SB20-5030-03		49.5 - 50.5	23	50		
99101-52	SB20-5230-03		51.5 - 52.5	23	50		

*建議使用扭力起子 · 參考6-22頁

5

高速搪刀